

# BVT-U Sizing Table



Inlet Diameter		Throat Diameter		Beta Ratio	Overall Length		Outlet Diameter		ΔP = Differential Pressure of 100" wc (24.864 kPa)						
(inches)	(mm)	(inches)	(mm)		(inches)	(mm)	(inches)	(mm)	Water Flow at 60 F (16 C)					ΔH = Headloss	
									US GPM	US MGD	LPS	m <sup>3</sup> /d	R <sub>D</sub> (10 <sup>-3</sup> )	in. wc	kPa
3.000	76.2	1.500	38.1	0.5000	7.60	193.0	2.30	58.4	130.42	0.188	8.23	710.91	123	9.5	2.36
3.000	76.2	1.800	45.7	0.6000	7.70	195.6	2.60	66.0	194.77	0.280	12.29	1061.70	183	6.7	1.67
3.000	76.2	2.100	53.3	0.7000	7.70	195.6	2.80	71.1	283.53	0.408	17.89	1545.51	267	4.2	1.04
4.000	101.6	2.000	50.8	0.5000	10.10	256.5	3.00	76.2	231.86	0.334	14.63	1263.84	164	9.2	2.28
4.000	101.6	2.400	61.0	0.6000	10.20	259.1	3.40	86.4	346.26	0.499	21.85	1887.46	245	6.5	1.61
4.000	101.6	2.800	71.1	0.7000	10.30	261.6	3.80	96.5	504.05	0.726	31.80	2747.58	356	4.0	1.01
6.000	152.4	3.000	76.2	0.5000	15.20	386.1	4.60	116.8	521.68	0.751	32.91	2843.65	246	8.7	2.17
6.000	152.4	3.600	91.4	0.6000	15.30	388.6	5.20	132.1	779.09	1.122	49.15	4246.79	367	6.2	1.53
6.000	152.4	4.200	106.7	0.7000	15.40	391.2	5.70	144.8	1134.11	1.633	71.55	6182.05	534	3.9	0.96
8.000	203.2	4.000	101.6	0.5000	20.20	513.1	6.10	154.9	927.42	1.335	58.51	5055.38	328	8.4	2.10
8.000	203.2	4.800	121.9	0.6000	20.40	518.2	6.90	175.3	1385.04	1.994	87.38	7549.86	489	6.0	1.48
8.000	203.2	5.600	142.2	0.7000	20.60	523.2	7.60	193.0	2016.20	2.903	127.20	10990.31	712	3.7	0.93
10.000	254.0	5.000	127.0	0.5000	25.20	640.1	7.70	195.6	1449.10	2.087	91.42	7899.03	409	8.2	2.04
10.000	254.0	6.000	152.4	0.6000	25.50	647.7	8.70	221.0	2164.13	3.116	136.54	11796.65	611	5.8	1.44
10.000	254.0	7.000	177.8	0.7000	25.70	652.8	9.50	241.3	3150.32	4.536	198.75	17172.35	890	3.6	0.90
12.000	304.8	6.000	152.4	0.5000	30.30	769.6	9.20	233.7	2086.70	3.005	131.65	11374.60	491	8.0	2.00
12.000	304.8	7.200	182.9	0.6000	30.60	777.2	10.40	264.2	3116.35	4.488	196.61	16987.18	734	5.7	1.41
12.000	304.8	8.400	213.4	0.7000	30.80	782.3	11.40	289.6	4536.46	6.532	286.21	24728.19	1068	3.5	0.88
14.000	355.6	7.000	177.8	0.5000	35.30	896.6	10.80	274.3	2840.23	4.090	179.19	15482.09	573	7.9	1.96
14.000	355.6	8.400	213.4	0.6000	35.70	906.8	12.10	307.3	4241.69	6.108	267.61	23121.44	856	5.6	1.39
14.000	355.6	9.800	248.9	0.7000	36.00	914.4	13.30	337.8	6174.62	8.891	389.56	33657.81	1246	3.5	0.87
16.000	406.4	8.000	203.2	0.5000	40.30	1023.6	12.30	312.4	3709.69	5.342	234.05	20221.51	655	7.8	1.93
16.000	406.4	9.600	243.8	0.6000	40.80	1036.3	13.90	353.1	5540.17	7.978	349.53	30199.43	978	5.5	1.36
16.000	406.4	11.200	284.5	0.7000	41.10	1043.9	15.30	388.6	8064.81	11.613	508.81	43961.23	1424	3.4	0.85
18.000	457.2	9.000	228.6	0.5000	45.40	1153.2	13.80	350.5	4695.08	6.761	296.21	25592.85	737	7.6	1.90
18.000	457.2	10.800	274.3	0.6000	45.90	1165.9	15.60	396.2	7011.78	10.097	442.37	38221.15	1101	5.4	1.35
18.000	457.2	12.600	320.0	0.7000	46.20	1173.5	17.20	436.9	10207.03	14.698	643.96	55638.43	1602	3.4	0.84
20.000	508.0	10.000	254.0	0.5000	50.40	1280.2	15.40	391.2	5796.40	8.347	365.70	31596.11	819	7.6	1.88
20.000	508.0	12.000	304.8	0.6000	51.00	1295.4	17.40	442.0	8656.52	12.465	546.14	47186.61	1223	5.3	1.33
20.000	508.0	14.000	355.6	0.7000	51.30	1303.0	19.10	485.1	12601.27	18.146	795.02	68689.41	1780	3.3	0.83
24.000	609.6	12.000	304.8	0.5000	60.50	1536.7	18.50	469.9	8346.81	12.019	526.60	45498.40	983	7.4	1.84
24.000	609.6	14.400	365.8	0.6000	61.20	1554.5	20.90	530.9	12465.38	17.950	786.44	67948.72	1467	5.2	1.30
24.000	609.6	16.800	426.7	0.7000	61.60	1564.6	22.90	581.7	18145.82	26.130	1144.82	98912.76	2136	3.3	0.81
30.000	762.0	15.000	381.0	0.5000	75.60	1920.2	23.10	586.7	13041.89	18.780	822.82	71091.25	1228	7.2	1.79
30.000	762.0	18.000	457.2	0.6000	76.50	1943.1	26.10	662.9	19477.16	28.047	1228.82	106169.87	1834	5.1	1.27
30.000	762.0	21.000	533.4	0.7000	77.00	1955.8	28.70	729.0	28352.85	40.828	1788.79	154551.18	2670	3.2	0.79
36.000	914.4	18.000	457.2	0.5000	90.70	2303.8	27.70	703.6	18780.32	27.044	1184.85	102371.39	1474	7.0	1.75
36.000	914.4	21.600	548.6	0.6000	91.80	2331.7	31.30	795.0	28047.11	40.388	1769.50	152884.61	2201	5.0	1.24
36.000	914.4	25.200	640.1	0.7000	92.40	2347.0	34.40	873.8	40828.10	58.792	2575.85	222553.70	3204	3.1	0.77
42.000	1066.8	21.000	533.4	0.5000	105.80	2687.3	32.40	823.0	25562.10	36.809	1612.72	139338.84	1720	6.9	1.72
42.000	1066.8	25.200	640.1	0.6000	107.10	2720.3	36.50	927.1	38175.24	54.972	2408.48	208092.94	2568	4.9	1.22
42.000	1066.8	29.400	746.8	0.7000	107.80	2738.1	40.10	1019	55571.58	80.023	3506.02	302920.32	3738	3.1	0.76
48.000	1219.2	24.000	609.6	0.5000	120.90	3070.9	37.00	939.8	33387.24	48.078	2106.41	181993.59	1965	6.8	1.69
48.000	1219.2	28.800	731.5	0.6000	122.40	3109.0	41.80	1062	49861.53	71.801	3145.77	271794.86	2935	4.8	1.20
48.000	1219.2	33.600	853.4	0.7000	123.10	3126.7	45.90	1165.9	72583.29	104.520	4579.29	395651.03	4272	3.0	0.75

This sizing table can be used as a guide to aid the user in choosing the proper BVT-U for a given application and reflects the most commonly-used sizes. Other sizes and special geometries are available, often at no additional cost. Depending on the details of your application, a more appropriate selection, or a more accurate estimation of the performance of a given selection, may be available. Wyatt Engineering encourages users to contact their local Wyatt-Badger representatives, or call us directly, for definitive sizing information.

### Incompressible

#### Flow Relationships:

$$\Delta P_N = 100 (Q_N / Q)^2$$

$$\Delta H_N = \Delta H (Q_N / Q)^{1.88}$$

$$Q_N = Q (\Delta P / 100)^{0.5}$$

For a 20.00" x 14.000" BVT-U, find

ΔP at 20 000 US GPM

ΔH at 20 000 US GPM

Q<sub>N</sub> at 750" wc

#### Solutions:

Found using the "Incompressible Flow Relationships"

$$\Delta P_N = 100 (20\,000 / 12\,601.27)^2 = 251.90" \text{ wc}$$

$$\Delta H_N = 3.3 (20\,000 / 12\,601.27)^{1.88} = 7.9" \text{ wc}$$

$$Q_N = 12\,601.27 (750 / 100)^{0.5} = 34\,510.00 \text{ US GPM}$$